



# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SOLVENT BASED GROUT SEALER

CH04

## **Section 1: Product Information**

Distributed By: Hydro-Force, 4282 S 590 W, Salt Lake City, Utah 84123  
Company Phone Number: 801-268-2673  
Emergency Phone Number: 800-535-5053 (Infotrac)  
Date Prepared: 4/1/2012

---

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)  
Fire: 2 Health: 1 Reactivity: 0

## **Section 2: Composition / Information or Ingredients**

<b>Hazardous Ingredient</b>	<b>CAS</b>	<b>OSHA PEL</b>	<b>OSHA HAZARD</b>
Petroleum Spirits	64742-48-9	177 p.p.m.	Acute
Perfluorinated Polymer		300 p.p.m.	Acute

## **Section 3: Hazard Identification**

### **Potential Health Effects**

This product may be harmful or fatal if ingested. Eye contact will be irritating. Repeated or prolonged skin exposure may be irritating. Inhalation of mist produced during use may irritate mucous membranes. There are no animal test data or information available to predict the human health effects of overexposure to this product. High vapor concentrations (greater than 1000 ppm) may cause headaches and dizziness, and are anesthetic.

### **Carcinogenicity Information**

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

## **Section 4: First Aid Measures**

### **Inhalation**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and call a physician.

### **Skin Contact**

Flush skin with soap and water after contact. Wash contaminated clothing before reuse.

### **Eye Contact**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if irritation persists.

### **Ingestion**

If swallowed, do not induce vomiting. Keep at rest and call a physician.

**MATERIAL SAFETY DATA SHEET**  
**PRODUCT NAME: SOLVENT-BASED GROUT SEALER CH04QT**

Page 2 of 4

**Section 5: Fire-Fighting Measures**

**Flammable Properties**

Flash Point 125 degrees Fahrenheit by TCC

**Fire and Explosion Hazards**

This product is combustible. It can form combustible mixtures at temperatures at or above the flashpoint. Material can accumulate static charges which can cause an incendiary electrical discharge. Empty containers retain such product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. If involved in a fire, the product can release small quantities of toxic hydrogen fluoride and carbonyl fluoride fumes.

**Extinguishing Media**

Use water spray to keep fire-exposed surfaces cool. In case of small fires, use water spray, foam, dry chemical or carbon dioxide to extinguish fire.

**Fire Fighting Instructions**

Evacuate personnel to a safe area. Keep personnel removed and upwind of fire.

Respiratory protection is recommended for firefighting personnel. Avoid breathing decomposition products.

**Section 6: Accidental Release Measures**

**Safeguards (Personnel)**

Review Fire Fighting Measures and Handling (Personnel) sections before proceeding with clean-up. Use appropriate Personal Protective Equipment during clean-up. Spill area will be slippery.

**Spill Clean Up**

Contain spill and salvage as much material as possible. Soak up with sawdust, sand, oil dry or other absorbent material. Shovel or sweep up.

**Section 7: Handling and Storage**

**Handling (Personnel)**

Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Do not aerosolize. Always provide good ventilation. Use only low pressure sprayers (less than 60 psi). Never use a "power painter" as they generate high pressure and aerosolize product. Wear NIOSH/MSHA approved respiratory protection.

**Handling (Physical Aspects)**

Wear appropriate protective equipment.

**Storage**

Store in a well-ventilated place. Keep container tightly closed. Keep away from open flames, heat, sparks, pilot lights, static electricity, and heated surfaces. Store at room temperature if possible or above 45 Fahrenheit. Use proper grounding procedures due to electrostatic accumulation hazard.

**MATERIAL SAFETY DATA SHEET**  
**PRODUCT NAME: SOLVENT-BASED GROUT SEALER CH04QT**

Page 3 of 4

**Section 8: Exposure Controls / Personal Protection**

**Engineering Controls**

Use only with adequate ventilation. Vent fumes outside work area. When applying as a spray, use exhaust ducts, fans, and other design features to minimize worker exposure to mists, vapors, and overspray.

**Personal Protective Equipment**

**Eye/Face Protection**

Wear safety glasses or coverall chemical splash goggles.

**Respirators**

Wear NIOSH/MSHA approved respiratory protection.

**Protective Clothing**

Where there is potential for skin contact, have available and wear as appropriate, impervious gloves, apron, pants and jacket.

**Exposure Guidelines**

Recommended exposure limit is 300 ppm for an 8 hour workday.

**Other**

Do not consume food, drink, or tobacco in areas where they may become contaminated by this material. Always wash hands thoroughly with soap and water before smoking.

**Section 9: Physical and Chemical Properties**

Boiling Point (oF).....346-406oF

Vapor Pressure (mmHg.).....1.2MM HG

Vapor Density (AIR=1).....5.2

Solubility in Water.....5%

Specific Gravity(H2O=1).....0.0759(60oF)

Percent Volatile by Volume...99%

PH (1% Solution).....NA

Appearance & Odor.....Clear liquid, little or no color - slight Alyphatic Solvent odor

**Section 10: Stability and Reactivity**

Chemical Stability Stable

Incompatibility Avoid strong oxidizers and water

Polymerization Will not occur

Other Hazards Decomposition: Heating above 392 Fahrenheit or in fire conditions may form toxic decomposition products. These products may cause severe eye, nose, throat, and lung irritation. Use adequate ventilation.

**Section 11: Toxicological Information**

**Acute Effects**

Petroleum Spirits are minimally toxic orally (LD50 > 10000 mg/kg) and are minimally toxic on skin (LD50 > 3160 mg/kg).

**Chronic Effects**

Vapor/aerosol concentrations for petroleum spirits above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

**MATERIAL SAFETY DATA SHEET**  
**PRODUCT NAME: SOLVENT-BASED GROUT SEALER CH04QT**

Page 4 of 4

**Section 12: Ecological Information**

Ecotoxicity: Petroleum Spirits may cause long-term adverse effects in the aquatic environment.

Biodegradation: Petroleum Spirits are expected to be readily biodegradable.

Hydrolysis: Petroleum Spirits Transformation due to hydrolysis not expected to be significant.

Photolysis: Petroleum Spirits Transformation due to photolysis not expected to be significant.

Atmospheric Oxidation: Petroleum Spirits expected to degrade rapidly in air

**Section 13: Disposal Considerations**

Contain with chemical absorbent material. Do not dispose of on the land, in surface waters, or in storm drains. Small spills and waste may be flushed into a waste treatment sewer where local regulations permit. Larger quantities should be collected for reuse or consigned to a licensed hazardous waste hauler for disposal in accordance with federal, state and local regulations. **All disposal must be in accordance with all federal, state and local regulations.**

**Section 14: Transportation Information**

**Ground Transportation:** Limited quantity exception applies for inner packaging less than 1.3 gallons. Requires limited quantity label.

**Air Transportation:** With a vented seal/cap, this item cannot be shipped via air in accordance with CFR 49 173-24(g).

**Maritime Transportation:** UN1268; Petroleum Distillates; NOS (Odorless Mineral Spirits), 3, PGIII; check for limited quantity values.

**Section 15: Regulatory Information**

Petroleum solvent (CAS# 64742-48-9) MASS, OSHA WAC, PA, TXAIR, WHMIS

All components are listed on TSCA

MASS = Massachusetts Hazardous Substance List

OSHA WAC = OSHA Workplace Contaminants

PA = PA Right-to-Know List of Hazardous Substances

TXAIR = Texas Air Contaminants with Health Effects Screening Level

WHMIS = Workforce Hazardous Material Information System

**Section 16: Other Information**

This product has no established regulatory information. All regulatory information given is based on individual components of the mixture by component number. While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. HYDROFORCE MANUFACTURING MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

N/A= Not applicable N/D= Not determined N/E= Not established