

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: QUICK FILLER  
CL050

## SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 4282 S 590 W, Salt Lake City, Utah 84123

Company Phone Number: 801-261-1282

Emergency Phone Number: 1-800-535-5053 (Infotrac)

Date Prepared: 4/1/08 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)

Fire: Health: Reactivity:

### 1. COMPOSITION/INFORMATION ON COMPONENTS

Mixture of alkyl phthalates and PVC.

### 2. HAZARD IDENTIFICATION

Health risks: exposure to the product does not involve any particular health risks.  
Contact with the eyes causes reddening, smarting and irritation.  
Swallowing can cause abdominal pain and nausea.  
Repeated inhalation of the vapours can irritate the respiratory system.

Environmental risks: -

### 3. FIRST AID in the event of:

Inhalation: move the person to an open well-ventilated environment and leave him/her to rest.

Skin contact: remove and wash all clothes contaminated by the product.  
Wash the skin with plenty of water and neutral soap.

Eye contact: wash eyes with plenty of water.  
If the irritation persists, seek medical advice.

Swallowing: If the irritation persists, seek medical advice.  
do not induce vomiting. Seek medical advice.  
Never force an unconscious person to drink.

#### 4. FIRE PRECAUTIONS

Suitable extinguishing products: chemical powders, alcohol-resistant foams, carbon dioxide, nebulised water (use water to cool containers exposed to fire).

Extinguishing products not to be used jets of water can spread the fire.  
for safety reasons:

Possible exposure risks combustion can produce acrid irritating fumes and

deriving from combustion products: carbon monoxide.

Special protective equipment wear protective fireproof clothing, including

for fire extinguishing personnel: breathing apparatus.

#### 5. PRECAUTIONS IN THE EVENT OF ACCIDENTAL LEAKAGE

Individual precautions: wear suitable clothing and protective waterproof gloves.

In poorly ventilated environments, adequately protect the respiratory system.

Environmental precautions: keep the product well away from refuse dumps, surface and underground water and the soil.

Cleaning methods: absorb the leak with inert materials (sand, earth, vermiculite, etc.) and mechanically collect in suitable containers.

Dispose of the waste in accordance with the law.

Wash the contaminated area with water.

Other precautions: avoid contact with strong oxidising agents, acids and bases. The product can accumulate electrostatic charges which, when released, can spark off fire.

#### 6. HANDLING AND STORAGE

Handling: Adopt all routine precautions for the handling of chemicals.

When using the product, keep well away from foodstuffs and items for consumption.

Avoid repeated and prolonged exposure. Do not smoke. The product tends to accumulate electrostatic charges and adequate earthing procedures should therefore be adopted.

Storage: the product must be kept in the original closed containers,

in a cool ventilated place, protected from sunlight, at a temperature not below 0°C and not exceeding 50°C.

## 8. EXPOSURE CONTROL/INDIVIDUAL PROTECTION

Respiratory protection:	for occasional use, employ in adequately ventilated environments.
Hand protection:	use protective waterproof gloves.
Eye protection:	use protective goggles.
Skin protection:	use protective clothing.
Specific hygiene precautions:	wash your hands at the end of work. Keep work clothes in a separate place. Do not smoke or eat during use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	milky oily liquid
Smell	slight
pH	not applicable
Initial boiling point	above 250°C
Autoinflammability	above 250°C
Flash point	above 150°C
Comburent properties	data not available
Vapour pressure	data not available
Relative density	approx. 1 g/ml (25°C)
Solubility in water	insoluble
Density of the vapours (air=1)	above 1

## 10. STABILITY AND REACTIVITY

Conditions to be avoided:	the product is normally stable. Avoid high temperatures and the accumulation of electrostatic charges.
Substances to be avoided:	the product is incompatible with strong oxidising agents, acids and bases.
Hazardous decomposition products:	thermal decomposition produces toxic compounds.

## 11. TOXICOLOGICAL INFORMATION

Inhalation:	symptoms: irritation of respiratory system.
Swallowing:	symptoms: irritation of mouth and throat, abdominal pain, headache, nausea, general weakness.
Skin contact:	symptoms: irritation of skin.
.Eye contact:	symptoms: irritation of eyes.

## 12. ECOLOGICAL INFORMATION

Use in accordance with good working practice, avoiding dispersion of the product in the environment.

## 13. DISPOSAL

Dispose of in compliance with current local and national regulations (Decree Law of 5<sup>th</sup> February 1997 no.22 and subsequent amendments).

Use of the product is subject to observance of the laws concerning hygiene and safety at work (Presidential Decree no. 203/88, Presidential Decree no. 303/56).

## 14. INFORMATION ON TRANSPORT

The product should be transported in its original containers or, in any case, in closed containers in order to avoid leaks, made of material that cannot be attacked by the content and cannot form harmful or dangerous combinations with the content.

In general, for transport adhere to the regulations currently in force, the recommendations of the ONU, ADR (by road), RID (by rail), IMO (by sea) and IATA (by air).

Road and rail transport (ADR/RID): not classified.

ADR: class 9, 11°C UN 3082

## 15. INFORMATION ON LAWS

Hazard labelling – Decree Law of 16th July 1998

The product contains:	-
Hazard indications:	-
Hazard warnings:	-
Precautions:	Keep out of the reach of children (S 2). If swallowed, seek medical advice immediately and show this container or label (S 46).

## 16. FURTHER INFORMATION

Main sources used in drawing up the sheet:

Sax, "Dangerous properties of industrial materials", 8th edition  
Handbook of toxic and hazardous chemicals and carcinogens

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

---

N/A = Not applicable N/D = Not determined N/E = Not established