

CL 058 / CLOCO MATTE

CMU

UNITERS

North America LLC

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAMES: SOFT FINISH MATTE
SOFT FINISH GLOSSY

CHEMICAL FAMILY: Nitrocellulose Lacquer in an aqueous emulsion

DISTRIBUTOR: UNITERS North America, LLC
P.O. Box 10909
West Palm Beach, FL 33419
Tel: (800) 601-9258
Fax: (561) 584-6558

MANUFACTURER: UNITERS S.p.A.
Via E. De Nicola, 1
36075 Montecchio Maggiore (VICENZA)
EMERGENCY TELEPHONE NUMBER:
(Tel) Italy: 0444-499099
(Fax) Italy: 0444-499106

2. COMPOSITION/ INFORMATION ON INGREDIENTS

Component	CAS#	% By Wt.	Exposure Limits
Butyl Acetate	123-86-4	5 - 15	150ppm TLV, 200ppm STEL
Xylene, mixed isomers	1330-20-7	5 - 10	100ppm TWA ACGIH
Nitrocellulose (<12.5% N)	9004-70-0	5 - 10	Not established

3. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

ROUTE(S) OF ENTRY.....: Skin and eye contact with liquid or inhalation of Vapor.

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

Butyl acetate is an irritant to skin, eyes and respiratory passages.

Xylene is an irritant to skin, eyes and respiratory system. Overexposure may cause headache, dizziness, drowsiness and nausea. Overexposure may cause Central Nervous System effects.



P.O. Box 10909, West Palm Beach, FL 33419

Phone: 800-601-6458 | Fax: 561-584-6558 | www.unifersna.com



CARCINOGENICITY:

NTP.....: No

IARC.....: No

OSHA.....: No

4. FIRST AID MEASURES:

SKIN: Remove contaminated clothing and shoes. Wash with soap or mild detergent and large amounts of water. Do not use solvents or thinners. Consult physician if irritation occurs.

EYES: Hold eyes open and flush for at least 15 minutes with large amounts of water. Seek immediate medical attention.

INGESTION: Do not induce vomiting. Give two glasses of water to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult physician immediately.

INHALATION: Remove to fresh air immediately. If breathing is difficult administer oxygen. Consult physician if irritation of respiratory passage occurs.

5. FIRE FIGHTING MEASURES

FLASH POINT: 73°F (23°C)

EXTINGUISHING MEDIA... Alcohol foam, carbon dioxide, dry powder, or water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing. Emits toxic oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES:

SPILL AND LEAK PROCEDURES: Remove all sources of ignition. Wear appropriate personal protective equipment; contain spills onto inert absorbent and place in suitable containers.

7. HANDLING AND STORAGE

STORAGE: Store closed containers in cool, dry area away from heat, direct sunlight, oxidizing agents, and strong acids and alkalis. Keep in a well-ventilated area suitable for flammable material storage.

HANDLING: Avoid inhalation of vapors, skin and eye contact. Do not eat, drink or smoke in application area. No sources of ignition should be in the area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Use local exhaust ventilation. Use in an area with controls and equipment suitable for handling flammable liquids.

RESPIRATORY PROTECTION: If airborne concentration exceeds recommended limits, use a NIOSH approved respirator in accordance with OSHA Respirator Protection requirements under 29 CFR 1910.134.

SKIN PROTECTION: Clothing suitable to prevent skin contact. Use butyl rubber gloves. Check suitability recommendations by protective equipment manufacturers, especially towards chemical breakthrough resistance.

EYE PROTECTION: Safety goggles with side shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:	Thick Liquid
COLOR:	White
ODOR:	Characteristic solvent
PH:	8.0 +/-0.5
SOLUBILITY IN WATER:	Soluble

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and other potentially toxic fumes.

POLYMERIZATION: Will not occur under regular conditions of use.

INCOMPATIBILITIES: Avoid strong acids, bases, and oxidizing agents.

11. TOXICOLOGICAL INFORMATION

See Section 3 - Human Effects and Symptoms of Overexposure

12. ECOLOGICAL INFORMATION

Avoid contamination of ground water or waterways. Do not discharge into sewers.

13. DISPOSAL CONSIDERATIONS

Incinerate or dispose of in accordance with Federal, State or Local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME.: PAINT RELATED MATERIAL (FLAMMABLE)
CLASS 3.2, UN 1263, PACKAGING GROUP III

15. REGULATORY INFORMATION

All components of this product are on the TSCA Inventory.

SARA Title III

This product contains xylene which is subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372

Note: Entries under this section cover only those regulations typically addressed in the MSDS generating process, such as, TSCA, and EPCRA/SARA Title III.

6. OTHER INFORMATION

HAZCOM LABEL: WARNING FLAMMABLE
CAUTION! IRRITANT TO SKIN, EYES AND RESPIRATORY PASSAGES.
 HARMFUL IF SWALLOWED

To the best of our knowledge, the information contained in this MSDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data

on this MSDS relate only to the specific material designated herein. We do not assume any liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

Revision Date: 07/13/10
