



MATERIAL SAFETY DATA SHEET

**PRODUCT NAME: AVENGE HEAVY DUTY FABRIC
PRESPRAY CU21**

SECTION 1: PRODUCT INFORMATION

PRODUCT NAME: Avenge Heavy Duty Fabric Prespray

Distributed by: Bridgepoint Systems

4282 S 590 W

Salt Lake City, UT 84123

Telephone: 801-261-1282

Prepared 2/1/2011

EMERGENCIES: (800) 535-5053 (Infotrac)

Hazard Rating (Zero=Insignificant 1= Slight 2= Moderate 3= High 4= Extreme)

Fire: 0 Health: 1 Reactivity: 0

SECTION 2: INGREDIENTS

PRINCIPLE HAZARDOUS INGREDIENTS:

Glycol Ether DB (CAS #112-34-5)

Triethanolamine (CAS # 102-71-6)

TLV

N/E

5 mg/m³

OSHA PEL

N/E

N/E

SECTION 3: HEALTH HAZARD INFORMATION

IMMEDIATE HEALTH EFFECTS

Eyes: Overexposure may cause irritation to eyes.

Skin: Prolonged and repeated contact may cause irritation to skin.

Inhalation: Inhalation may cause irritation of upper respiratory passages.

Ingestion: Single dose oral toxicity is low. Swallowing large amounts may be harmful.

PRIMARY ROUTES OF ENTRY: Eyes, skin contact/absorption, inhalation or ingestion.

SIGNS/SYMPTOMS OF OVEREXPOSURE: Gastrointestinal irritation (nausea, vomiting, diarrhea), and/or irritation to the skin, eyes, nose, throat, and respiratory tract.

TARGET ORGAN EFFECTS: Irritation of the skin and eyes. Irritation of lungs possible if mists/aerosols are inhaled.

REPRODUCTIVE/DEVELOPMENTAL INFORMATION: No data available.

CARCINOGENICITY:

NTP: Known – No; Anticipated – No

OSHA: No

IARC: No

LONG TERM EFFECTS: No data available.

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush eyes with water for at least 15 minutes. If irritation persists, consult a physician.

SKIN: If irritation occurs, flush skin with water for at least 15 minutes. If irritation persists, consult a physician

INHALATION: If symptoms of overexposure develop, remove to fresh air. If symptoms persist, consult a physician.

INGESTION: Give 8 to 16 ounces of water to dilute substance. Do not induce vomiting. Consult a physician or local Poison Control Center. Never give anything by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET
PRODUCT NAME: AVENGE HEAVY DUTY FABRIC PRESpray

CU21

Page 2 of 4

SECTION 5: FIRE, EXPLOSION & REACTIVITY DATA

FLASHPOINT (° Fahrenheit): No flash below boil.

EXPLOSIVE LIMITS: No data available.

AUTOIGNITION TEMPERATURE: No data available.

EXTINGUISHING MEDIA: Water spray, foam, dry chemical powder of carbon dioxide.

FIRE FIGHTING INSTRUCTIONS: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece operated in positive pressure mode. Move containers from fire area if it can be done without risk. Use water to keep fire-exposed containers cool.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SMALL SPILL: For small spills, soak up material with an absorbent such as clay, sand, or other suitable material and dispose of properly. Flush area with water to remove trace residue.

LARGE SPILL: Dike and contain spilled material. Remove with vacuum trucks or pump to storage/salvage containers. Soak up residue with an absorbent such as clay, sand, or other suitable material. Flush area with water to remove trace residue.

Also note: Surfaces can become slippery if spilled; tread carefully to avoid falling hazard.

SECTION 7. PRECAUTIONS FOR HANDLING AND STORAGE

Store out of reach of children. Keep container closed. Store in a cool, dry location. Avoid freezing or extended storage in high temperatures.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Limits..... None established.

Ventilation System..... Room ventilation is normally satisfactory. Mechanical assist may be required when vapors or mist are generated..

Personal Respirators..... For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH approved) may be worn.

Skin Protection..... Wear protective gloves and clean body-covering clothing.

Eye Protection..... Use chemical safety goggles.

SECTION 9: PHYSICAL DATA

Physical State: Liquid

pH (RTU) 9.8 to 10.2

Color: Clear

Solubility in Water.....Complete

Odor: Slight floral scent

Boiling Point: 212 F

Specific Gravity: 8.45 lbs/gal

Percent Volatile by Volume: N/D

Vapor Pressure(mmHg.): N/D

Vapor Density(AIR=1): N/D

SECTION 10. STABILITY AND REACTIVITY

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition or Byproducts: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids and other unidentified thermal decomposition products from this product or its packaging.

Hazardous Polymerization: Will not occur.

Incompatibilities: Acid materials and strong oxidizing materials.

Conditions to Avoid: None known

MATERIAL SAFETY DATA SHEET
PRODUCT NAME: AVENGE HEAVY DUTY FABRIC PRESpray
CU21

Page 3 of 4

SECTION 11. TOXICOLOGICAL INFORMATION

Glycol Ether DB – Oral guinea pig LD50: 2000 mg/kg. Dermal Rabbit LD50: 2700 mg/kg.
Triethanolamine

Acute Toxicity - Ingestion

Single dose oral LD50 has not been determined. For the major component(s): LD50, Rat 5,000 - 9,600 mg/kg

Skin Absorption

The dermal LD50 has not been determined.

For the major component(s): LD50, Rabbit > 2,000 mg/kg

Sensitization

Skin

For the major component(s): Skin contact may cause an allergic skin reaction in a small proportion of individuals. For the major component(s): Did not cause allergic skin reactions when tested in guinea pigs.

Repeated Dose Toxicity

For the major component(s): In animals, effects have been reported on the following organs: Kidney. Liver.

Chronic Toxicity and Carcinogenicity

Contains component(s) which have caused cancer in laboratory animals. However, the relevance of this to humans is unknown.

Developmental Toxicity

Screening studies in animals suggest that this material does not affect fetal development.

Genetic Toxicology

In vitro genetic toxicity studies were negative.

SECTION 12. ECOLOGICAL INFORMATION

Glycol Ether DB

Acute Aquatic Effects Data: 24 h LC-50 (goldfish): 2700 mg/L 96 h LC-50 (bluegill sunfish): 1300 mg/L

Triethanolamine

Material is readily biodegradable. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50 >100 mg/L in the most sensitive species tested).

SECTION 13. DISPOSAL CONSIDERATIONS

Do not dispose of on the land, in surface waters, or in storm drains. Small spills and waste may be flushed into a waste treatment sewer where local regulations permit. Larger quantities should be collected for reuse or consigned to a licensed hazardous waste hauler for disposal in accordance with federal, state and local regulations. **All disposal must be in accordance with all federal, state and local regulations.**

MATERIAL SAFETY DATA SHEET
PRODUCT NAME: AVENGE HEAVY DUTY FABRIC PRESpray
CU21
Page 4 of 4

SECTION 14. TRANSPORTATION

No restrictions for Ground, Air, or Maritime Transportation in accordance with 49 CFR parts 100-185.

SECTION 15. REGULATORY INFORMATION

US Federal Regulations:

TSCA Status: The intentional components of this product are listed.

SARA - Section 313 (Toxic Chemical Release Reporting) 40 CFR 372 –Glycol Ether DB Listed.

SECTION 16. OTHER INFORMATION

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

N/A= Not applicable N/D= Not determined N/E= Not established